



ASHOK LEYLAND

Koi Manzil Door Nahin

ecomet^{STAR} 1215HE

The new 12 ton ecomet range is engineered to carry heavy loads with ease, to lower maintenance cost and to give higher savings per trip



Class leading payload
across variant



Heavy duty and
reliable aggregates



Cable shift CSO for
reduced gearshift
efforts



Wide load
body



Lube for life
propeller shaft



Unilever clutch actuation
system for lower effort
and high reliability



HINDUJA GROUP

ecomet^{STAR}



Improved
turnaround time



Full front
metal fascia



New powerful round
headlamps – 2x illumination



Higher driver
safety



Easy
reparability

ASHOK LEYLAND i-Gen6 ADVANTAGE

Over the years, Ashok Leyland Ltd., strove to deliver performance beyond excellence with inline or 'SAADA' pump for BS-III and iEGR technology for BS-IV. Now with BS-VI, taking the proven iEGR technology up a notch, we are introducing the i-Gen6 engine technology which enhances the engine performance and durability further. With lower DEF consumption and compact design, i-Gen6 lowers the cost of operation per ton-km, offering better fluid efficiency and low maintenance. The unique Mid-NOx strategy ensures overall lower cost of ownership as compared to competition.

Innovative



Improved efficiency -

- Controls NOx generation in the engine itself



Lower TCO -

- Lower Diesel Exhaust Fluid (DEF) consumption
- Lower operational cost

Intelligent



Simple functioning -

- Lesser number of sensors



Improved EATS life -

- Lower maintenance cost

Indian



Mid-NOx technology

- iEGR + SCR
- Higher fluid efficiency



Highly robust -

- Best suited for Indian driving conditions

- Superior mileage: Proven iEGR engine with improved air intake & radiator offer higher performance
- Longer active regeneration intervals - ensures longer DPF life.
- Inline EATS: Allows flexibility in packaging / better space utilisation
- Larger (24L) Diesel Exhaust Fluid (DEF) tank : Coupled with lower consumption, ensures less frequent DEF refills
- First pipe length is 0.8 m: Best-in-class thermal management.



H4 - 110 kW (150 HP), 450 Nm
fuel efficient engine



Advanced EATS (Engine After
Treatment System)

SPECIFICATIONS

Cabin	Ecomet Day					
Engine type	H series 4 cylinder with i-Gen6 technology					
Maximum power	110 kW (150 HP) @ 2400 rpm					
Maximum torque	450 Nm @ 1250-2000 rpm					
Clutch	330 mm dia - single plate, dry type with clutch booster					
Gearbox type	6 speed synchromesh ODGB, cable CSO system ZF6S36 OD GB – FGR 8.28:1 (3250mm / 3970mm / 4200mm WB) ZF5636 OD – FGR 6.93:1 (4750mm / 5200mm WB)					
Propeller shaft	Heavy Duty Monotron Propeller Shaft					
Rear axle	Fully floating single speed rear axle, Hypoid, RAR 5.57:1					
Front axle	Forged I section - Reverse Elliot type					
Steering	Integral power steering					
Frame	204mm x 76mm x 6mm					
Front suspension	Semi-elliptic multileaf					
Rear suspension	Semi-elliptic multileaf					
Brakes	Full air dual line. Parking brakes on rear wheels only					
Fuel tank	185 L metal tank					
DEF tank	24 L capacity					
Electricals	12 V, 120 AH, Alternator – 90 A					
Tyre	8.25R20 16 PR 8.25X16 16PR					
GVW	11,990 kg					
Wheel base	3250mm	3970mm	4200mm	4200mm	4750mm	5200mm
Loading span	4.3m	5.2m	5.8m	6.1m	6.7m	7.3m

PRODUCT APPLICATIONS

Parcel and logistics 	Market load 	Fruits / Vegetables 	Food grains 	White goods 	Dairy 	Cement 	Auto parts 	Industrial goods 
---	--	--	--	--	--	---	---	---

FEATURES



Innovative, intelligent and indigenous i-Gen6 engine with Mid-NOx technology



NextGen i-alert (Fleet management, fuel monitoring, e-diagnostics, remote access)



GSAS (Gear Shift Advisory System)



4 years / 4,00,000 km warranty



USB Charger



New digital display




Rear LED Tail Lamp

VARIANTS

Model		4.3m	5.2m	5.8m	6.1m	6.7m	7.3m
ecomet 1215	CBC	✓	✓	✓	✓	✓	✓
	FSD		✓	✓		✓	
	DSD		✓			✓	
	HSD		✓	✓	✓	✓	✓

BODY OPTIONS



Cab chassis



Fixed side deck

Body	L	B	H
Standard	L	2260mm	593mm



Drop side deck

Body	L	B	H
Standard	L	2306mm	591mm



High side deck

Body	L	B	H
Standard	L	2260mm	1105mm

Length	4432mm/ 5287mm 5810mm/ 6096mm 6768mm/ 7315mm		
--------	--	--	--



ASHOK LEYLAND
Koi Manzil Door Nahin

Registered Office - Ashok Leyland Limited, No. 1, Sardar Patel Road, Guindy, Chennai - 600032, Tel. - 91 44 2220 6000
E-mail - reachus@ashokleyland.com | Website - www.ashokleyland.com

HELPLINE
1800-266-3340

AUTHORISED DEALER



HINDUJA GROUP